(http://conference.ui.ac.id/icgh/icgh2018/login)

(http://conference.ui.ac.id/icgh/icgh2018/login)

(http://conference.ui.ac.id/icgh/icgh2018/login)Home (http://conference.ui.ac.id/icgh/icgh2018/index) > User

(http://conference.ui.ac.id/icgh/icgh2018/user) > Author (http://conference.ui.ac.id/icgh/icgh2018/author) > Submissions

(http://conference.ui.ac.id/icgh/icgh2018/author) > #16895 (http://conference.ui.ac.id/icgh/icgh2018/author/submission/16895) > Paper Review

(http://conference.ui.ac.id/icgh/icgh2018/author/submissionReview/16895)

#16895 Paper Review

Summary (http://conference.ui.ac.id/icgh/icgh2018/author/submission/16895)

Review (http://conference.ui.ac.id/icgh/icgh2018/author/submissionReview/16895/1)

Submission

Authors Dewi Puspitasari 📺 (http://conference.ui.ac.id/icgh/icgh2018/user/email?

redirectUrl=http%3A%2F%2Fconference.ui.ac.id%2Ficgh%2Ficgh2018%2Fauthor%2FsubmissionReview%2F16895&to%5B%5D=%22Dewi%20Puspitasari%22%20%3CDewident%40gmail.cc

Title Effect of Storage Temperature on Degree Of Conversion and Surface Hardness of Bulk Fill Composite Resin

Track Dentistry Papers

DirectorYuniardini Wimardhani 🛅 (http://conference.ui.ac.id/icgh/icgh2018/user/email?

redirectUrl=http%3A%2F%2Fconference.ui.ac.id%2Ficgh%2Ficgh2018%2Fauthor%2FsubmissionReview%2F16895&to%5B%5D=Yuniardini%20Wimardhani%20%3Cjuneardini%40gmail.com

Peer Review

Review Version	16895-30654-1-RV.DOCX (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/30654/1) 2018-07-09
Initiated	2018-08-19
Last modified	2018-10-18
Uploaded file	Reviewer A 16895-35392-1-RV.DOCX
	(HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/35392/1) 2018-08-19
Director Version	16895-39512-1-DR.RAR (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/39512/1) 2018-10-13
	16895-39512-2-DR.ZIP (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/39512/2) 2019-02-20
Author Version	16895-35881-1-DR.DOCX (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/35881/1) 2018-08-21
	16895-35881-2-DR.DOCX (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/35881/2) 2018-10-18
	16895-35881-3-DR.DOCX (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/35881/3) 2019-04-08

Director Decision

Decision	Revisions Required 2018-10-13
Notify Director	(http://conference.ui.ac.id/icgh/icgh2018/author/emailDirectorDecisionComment?paperId=16895) Director/Author Email Record 2019-04-08
Director Version	16895-39512-1-DR.RAR (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/39512/1) 2018-10-13 16895-39512-2-DR.ZIP (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/39512/2) 2019-02-20
Author Version	16895-35881-1-DR.DOCX (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/35881/1) 2018-08-21 16895-35881-2-DR.DOCX (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/35881/2) 2018-10-18 16895-35881-3-DR.DOCX (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/35881/2) 2018-10-18 16895-35881-3-DR.DOCX (HTTP://CONFERENCE.UI.AC.ID/ICGH/ICGH2018/AUTHOR/DOWNLOADFILE/16895/35881/2) 2019-04-08
Upload Author Version	Choose File No file chosen Upload

Layout

Galley Format	FILE	VIEWS
		None
Supplementary Files	FILE	
		None

(http://creativecommons.org/licenses/by/3.0/)

This work is licensed under a Creative Commons Attribution 3.0 License (http://creativecommons.org/licenses/by/3.0/).

Copyright 2019 © ICGH in conjunction with AIC-HHC

EFFECT OF STORAGE TEMPERATURE ON DEGREE OF POLYMERIZATION AND SURFACE HARDNESS OF BULK-FILL COMPOSITE RESIN

Dewi Puspitasari, DDS, MSc¹, Adianto Prasetyo¹, Muhammad Deni Rahman¹, Sherli Diana, DDS, MClinDent², Muhammad Yanuar Ichrom Nahzi, DDS, MClinDent²

¹ Department of Dental Materials
Faculty of Dentistry, University of Lambung Mangkurat
² Department of Conservative Dentistry
Faculty of Dentistry, University of Lambung Mangkurat

Corresponding author:

Dewi Puspitasari

Department of Dental Materials

Faculty of Dentistry, University of Lambung Mangkurat, Indonesia

E-mail: <u>dewident@gmail.com</u>

Short title: Storage temperature of bulk-fill composite resin

Commented [Editor1]: Remark: Consider revising this to "EXTENT OF POLYMERIZATION" OR "DEGREE OF POLYMERIZATION" throughout the manuscript.

Commented [Editor2]: Remark: According to the guidelines, academic degrees of all authors should be provided.

Commented [DP3R2]: We have added the academic degrees of all author

ABSTRACT

Increasing or decreasing the storage temperature of bulk-fill composite resin can prolong its shelf life and improve its ease of application. Storage temperature may affect polymerization and mechanical properties, such as degree of polymerization and hardness. We analyzed the effect of storage temperature on degree of polymerization and surface hardness of bulk-fill composite resin by storing it for 24 h at three different temperatures before testing: at 5°C, at 25°C, and at 35°C. Thirty-six specimens of composite resin were placed into a Fourier transform infrared spectrometer to analyze degree of polymerization; another 24 specimens of resin were tested for hardness using a hardness tester. By analyzing results with a one-way ANOVA and LSD post hoc test, we determined that temperature did not significantly affect degree of polymerization but hardness significantly differed between treatments when compared using a Vicker's hardness number (VHN). The highest mean VHN occurred at 35°C (VHN = 53.86 ± 0.79), followed by 25°C (VHN = 51.94 ± 0.41), and the lowest at 5°C (VHN = 49.22 ± 0.57). Therefore, elevating the storage temperature of bulk-fill composite resin before use may not affect degree of polymerization but will increase surface hardness.

Key Words: dental resin, polymerization

INTRODUCTION

Composite resins are widely used in dental practices to re-establish form, function, and aesthetics of teeth and thus, have become an integral part of the modern, esthetic dentistry.^{1,2,3}

Commented [Editor4]: Remark: We have extensively edited this section to reduce the word count to <200 (currently 193) word: as specified by the journal. Please check.

Composite resins have undergone several improvements since they were introduced in 1962.⁴ Recently, there have been significant improvements in dental resins (particularly in bulk-fill composite types⁵), which have reduced the time and effort required to apply them. These new types of bulk-fill resins can be cured or polymerized into a single, 4-mm-thick layer, which is considerably more preferable than the technique required for applying traditional resins, which require incremental applications that have to be cured layer by layer in \leq 2-mm thicknesses.^{6,7} Layer-by-layer application is more time-consuming and creates gaps between resin layers, which results in weaker bonds and contamination between layers.^{6,7,8} Other advantages of bulk-fill composite resins are that they inadequately polymerize and transmit more light.^{6,7,9}

Polymerization is defined as a chemical reaction that converts monomers into a polymer chain structure.¹¹ Inadequate polymerization can result in resin shrinkage after polymerization and a reduction in resistance to wear.¹⁰ More complete polymerization would maximize the physical, mechanical, and biocompatibility benefits of composite resins.⁶ However, not all monomers in composite resins can be converted to polymers during polymerization, which results in unsaturated free monomers (unreacted monomers) in the final product. The amount of unconvertable monomers in the initial product affects its degree of polymerization.¹² The extent to which a monomer is polymerized is determined by the number (or percentage) of double carbon bonds (C=C) that it possesses, which are then converted during polymerization to a single carbon bond (C-C) needed to build a polymer chain.^{12,13} A lower degree of polymerization means that fewer monomers become bound to the polymer. Furthermore, a lower degree of polymerization in dental restoration results in inferior mechanical properties, greater discoloration and degradation, poorer wear resistance,

Commented [Editor5]: Remark: Introduced in the year? Consider specifying.

Commented [Editor6]: Remark: Consider defining this before information on inadequate polymerization in the previous paragraph.

Commented [DP7R6]: We have reorder the sentences

Commented [Editor8]: Remark: Do you mean in restored teeth or in the dental work?

Commented [DP9R8]: Dental restoration

and lower color stability.⁷ In contrast, a higher degree of polymerization improves the physical and mechanical properties of a composite resin.^{14,15} An important mechanical property is surface hardness, defined as the material's resistance to permanent penetration or indentation. This property is used to evaluate wear resistance, particularly where a surface encounters large amounts of masticatory forces, such as in posterior stress-bearing areas; polishability; and abrasive effects on antagonist teeth.^{8,11, 16,17}

Composite resins should be capable of being stored for long periods (i.e., possess a long shelf life) without compromising their physical and mechanical properties.¹⁴ Shelf life is specified by resin manufacturers as the time period during which the material remains suitable for use.¹⁸ Dentists store composite resins in refrigerators to prolong their shelf lives, usually at temperatures ranging from 2°C to 5°C.¹⁹ Such cooled composite resins are often immediately used after being taken from a refrigerator.¹⁴ However, a dental resin should be removed an hour or more before its planned use to allow it reach room temperature due to anticipating alteration the properties of polymerized composite resin.^{20,21} In addition, several dentists also increase the temperature of composite resins to improve their malleability, which reduces the viscosity of the material. Lower viscosity of a composite resin enables an easier application, improves marginal adaptation to cavity walls, and reduces microleakages.^{12,20,21}

Several studies have reported that storage temperature may affect the polymerization reaction of composite resins restoration.³ One study examined the mechanical properties of composite resins stored in a 37–40 °C oven to simulate high temperatures associated with exposure to direct sunlight or storage under ambient conditions in warm climates or during

Commented [Editor10]: Remark: Check whether you mean "amounts" here. Commented [DP11R10]: yes

Commented [Editor12]: Remark: Consider specifying why returning a resin to room temperature is important.

Commented [Editor13]: Remark: Are you referring to the process of producing resins (you said polymerization reaction) or do you mean that storage temperature affects polymerization after a resin has been produced? Please clarify.

Commented [DP14R13]: storage temperature may affect th

warm seasons. ^{14,22} However, it is not entirely clear how warm storage temperatures affect the characteristics of composite resins (e.g., their degree of polymerization and surface hardness). Therefore, the aim of this study was to analyze the degree of polymerization and surface hardness of composite resins stored under various temperature regimes: in a refrigerator, at ambient room temperature, and in a warming oven.

METHODS

Thirty-six specimens of bulk-fill composite resin (Tetric® N Ceram) were tested for degree of polymerization (18 samples were not polymerized for initial absorbance and 18 sample were polymerized and tested for absorbance, each divided into three treatments of six samples each). Twenty-four specimens of composite resin were tested for hardness (three treatments each of eight samples each). All test specimens were fabricated into cylinders 5 mm in diameter and 4 mm in height, following the manufacturer's instructions and the International Standards Organization 4049 specifications for split resin molds. All specimens had been approved for ethical clearance (038/KEPKG-FKGULM/EC/IX/2017) before testing.

The bulk-fill resins specimens were subjected to three storage conditions for a 24-h period: Treatment I (refrigerated at 5°C), Treatment II (maintained at an ambient room temperature of 25°C), and Treatment III (kept in a warmed oven at 35°C). After 24 h, the composite resin samples were removed from storage and immediately inserted into a resin mold before its storage (treatment) temperature changed appreciably. A Mylar strip was applied to the top of each specimen. Then each specimen was polymerized by positioning the tip of an LED light (intensity 850 mw/cm²) in contact with the Mylar strip for 20 s. (This

Commented [Editor15]: Remark: This sentence is out of place without some context and does not provide any pertinent information. If you use the sentence, explain its context.

Commented [Editor16]: Remark: This is confusing because you defined polymerization as a chemical reaction that converts monomers into a polymer chain structure, but then you have 18 seemingly already polymerized specimens. Are you referring to twi different types of polymerizations: one to make the polymer and another to harden it under LED light?

Commented [DP17R16]: 18 samples were not polymerized for initial absorbance and 18 sample were polymerized and tested for absorbance, subsequently each sample result is calculated based on the formula to obtain percentage of degree of polymerization

Commented [Editor18]: Remark: Note that the highlighted text was unclear and so we have edited it as per our understanding Check whether your intended meaning is retained.

irradiation method was based on the manufacturer's instructions). After being polymerized, the specimens were stored for 24 h in a saline-filled container on an incubator before being test. The list of composites resin compositions and manufacturers are provided in ^{7,24}

The degree of polymerization test

Eighteen specimens were used to test for initial absorbance characteristics by inserting the stored composite resin immediately into mold after removing them from storage, but not polymerizing them. The 18 other specimens were tested for absorbance characteristics after polymerizing them in molds. To measure degree of polymerization, each specimen was placed into a Fourier transform infrared spectrometer (FTIR) that had been equipped with an attenuated total reflectance (ATR) Diamond Accessory (Bruker Alpha). ATR was used to test degree of polymerization composite specimens not polymerized, whereas the polymerized composite specimens were tested for absorbance characteristics after polymerized absorbance values were recorded at wavelengths of 500–4000 cm⁻¹.⁴

The obtained absorbance data were converted to percentages of unreacted carbon double bonds in the resin. The percentage of unreacted carbon-carbon bonds (C=C) were determined by comparing the ratio of absorbance intensity of aliphatic (C=C) bonds (peak = 1637 cm^{-1}) against a baseline by using software or peaks of internal reference aromatic C=C (peak heights at 1608 cm^{-1}) both before and after polymerization of the specimens.^{4,11} The degree of polymerization (%DP) was established by subtracting the percentage of double carbon bonds from 100%, according to the formula:

Commented [Editor19]: Remark: We have extensively edited this section for better clarity. Check our edits carefully.

Commented [Editor20]: Remark: Please check the accuracy of word choice.

$$\% DP = \left\{ 1 - \frac{Abs \left(1637 \ cm^{-1} / 1608 \ cm^{-1} \right) polymerized}{Abs \left(1637 \ cm^{-1} / 1608 \ cm^{-1} \right) unpolymerized} \right\} \times 100$$
(1)

wherein Abs 1637 cm⁻¹ is aliphatic C=C absorbance at 1637 cm⁻¹ and Abs 1608 cm⁻¹ is aromatic C=C absorbance at 1608 cm⁻¹.

The surface hardness test

The specimens of composite resin stored in the incubator for 24 h were removed and immediately tested for hardness. Hardness was tested using the Vickers hardness (VH) test in a hardness-testing machine [Micro Vickers Hardness Tester (Buehler® Micro Hardness Tester, USA)]. The VH Tester is equipped with a Vickers diamond, which has a pyramidal diamond microindentor of 136° (where the two diagonals of the indentation left in the surface of the material are measured). The top of each surface of the specimen was divided into four equal quadrants. One indentation was made in each quadrant by the hardness-testing machine, which applied pressure at 300 gf for 15 s to each test point (one indentation per quadrant). Mean hardness values for the four test points (per specimen) were calculated for each surface, based on the Vicker's hardness number (VHN).^{7,11} VHN was calculated based on the formula:

$$VHN = \frac{1.854}{(\frac{d1+d2}{2})^2} F$$
(2)

wherein F was the load applied (gf), d was the mean length of the diagonals (m), and 1.854 was a constant. All test data for degree of polymerization and hardness were statistically

Commented [Editor21]: Remark: Please define what diagonals you mean.

Commented [DP22R21]: where the two differences of the indentation left in the surface of the material are measured

analyzed with one-way Analysis of Variance (ANOVA) using a confidence interval of 95%, followed by a post hoc LSD test.

RESULTS

Degree of polymerization (DP) test

We found that the highest mean value for degree of polymerization (38.17%) occurred in the bulk-fill composite resin treatment stored at 35°C, whereas the lowest mean value (36.67%) occurred in the 5°C storage treatment (Table 2). However, the one-way ANOVA showed that storage temperature was not related to degree of polymerization for bulk-fill composite resin (P = 0.454) (Table 2).

Vicker's hardness (VH) test

The measured surface hardness values are listed in Table 3. Along with the elevating temperature 5°C (VHN = 49.22 \pm 0.57), 25°C (VHN = 51.94 \pm 0.41) and 35°C (VHN = 53.86 \pm 0.79) showed that VHN also increased and was significantly different (P = 0.000) from one to another among temperature storage treatment, with the hardest composite resins created under the highest temperatures (Table 3).

DISCUSSION

We found that storage temperatures from 5°C to 35°C exhibited a slight increase in degree of polymerization (DP), even though the differences were not statistically different. Several researchers have found that high storage temperatures accelerate the photo-

Commented [Editor23]: Remark: Spell out all abbreviations in the main text at their first instance prior to submission.

polymerization reaction so that much more monomers are converted to polymers, causing an increase in thermal energy of molecules at the subatomic scale, which in turn might improve molecular mobility.^{15,25} Our finding is in line with Lohbauer (2009) and Tauböck (2015), both of whom recorded no significant differences in DP resin composites preheated at 68°C, 54°C, or stored at room temperature.^{19,26} However, Tauböck (2015) did not store their composite resins at a constant temperature before increasing the temperature to insert them into a mold for testing (to simulate a clinical scenario¹⁹). There is a time delay between removing resin from a heating device, dispensing it, inserting it into a prepared teeth, contouring it, and subsequently light-curing it, and so a decline in composite temperature during handling might have prevented a sufficient intensification in the polymerization reaction and enhancement in monomer conversion in their tests.²⁷ Previous studies have shown that resin temperature declines during the 40 s interval from removing a resin from storage to prepared teeth.²⁸ Furthermore, composite resins cured at different temperatures have been reported to exhibit similar polymer network crosslinking, determined from measurements of their glass transition temperatures.^{18,28}

The degree of polymerization and other properties may also vary among resin brands and shades.²⁸ Factors such as irradiation time, light source, power density, wavelength of the light source, tip size of light guide, light distance, and composition may all influence DP.¹¹ The minimum DP for composite resins has not yet been established for clinically acceptable restoration.⁷ Collares (2014) stated that DP values should be at least 55% for restoring teeth. In our study, DP ranged from 36% to 39%. This difference could be related to the variations in the method of measurement, specimen thickness, or irradiation intensity.¹³ **Commented [Editor24]:** Remark: Provide citations to these studies.

Commented [DP25R24]: we have added citation (28)

Commented [Editor26]: Remark: Please clarify as "from storage to ..."

Commented [Editor27]: Remark: We suggest that you reorde the sentences in this paragraph as follows: The degree of conversion and other properties may vary among resin brands and shades.²⁸ Factors such as irradiation time, light source, power density, wavelength of the light source, tip size of light guide, light distance, and composition may all influence DC.¹¹ The minimum DC for composite resins has not yet been established for clinically acceptable restoration.⁷ However, Collares (2014) stated that DC values should be at least 55%¹³. In our study, DC ranged from 36– 39%. This difference could be related to the variations in the method of measurement, specimen thickness, or irradiation intensity.¹³

Commented [Editor28]: Remark: At least 55% for what? For restoring teeth? Please specify.

The larger the atomic size and weight, the slower the speed of the atomic vibration amplitude and the slower the polymerization reaction rate. The matrix resin of bulk to fill Tetric® N Ceram is a mixture of bisphenol A diglycidyl ether dimethacrylate (Bis-GMA) and urethane dimethacrylate (UDMA), but its composition is dominated by Bis-GMA, which is comprised of larger and heavier molecules than other matrix resins.²⁴ Bis-GMA is assumed the most viscous monomer currently available, due to the strong hydrogen bonding of its hydroxyl groups (-OH) on its carbon backbone and the existence of aromatic rings in its structure.13,29 The monomer UDMA in Tetric® N Ceram is a viscous monomer, but the viscosity of UDMA is much lower and more flexible than Bis-GMA due to the weak hydrogen bond of its amine group relative to its hydroxyl groups.¹⁴ That is why the DP of Bis-GMA varied from 32.7% to 78.50% from previous study; lower DP values at higher Bis-GMA ratios can be attributed to higher viscosity. Therefore, increasing the concentration of Bis-GMA can lower the mobility of monomers in the polymerizing bulk.^{13,30} Tetric® N Ceram also contains of germanium-based photoinitiator Ivocerin, which is characterized by more intensive light absorption in the visible range and higher photoreactivity than the photosensitizer camphorquinone.8,19,31,32

In our study, elevating storage temperatures from 5°C to 35°C resulted in significant increases in VHN values (from 49.2 to 53.9). These VHN values were not much different than those found by Leprince (2014) (47.7), Jafarzadeh-Kashi (2015) (53.0), and Dionysopoulos (2016) (42.8) for bulk-fill composite resins.^{33,34,35} Some authors believe that a VHN exceeding 50 VHN is ideal for composite resins.¹¹ However, many other factors are known to affect VHN scores: the intensity of light used, curing time, incubation time, distribution of filler particle shapes, size and densities, type of monomers and their

Commented [Editor29]: Remark: Please check the accuracy of the edit

Commented [Editor30]: Remark: It is unclear whether this refers to the present study's findings or those of previous study/studies. Please clarify

Commented [DP31R30]: We have added "from previous study"

Commented [Editor32]: Remark: Lower than what? Please specify.

Commented [Editor33]: Remark: Difference relative to what? Please specify.

Commented [Editor34]: Remark: Incubation length or temperature? Please specify.

compositions, degree of polymer crosslinking, and type of photoinitiators used.¹¹ Preheating and precooling composite resins after storage could affect VHN, but the affect mainly depends on the type of composite resin used, depth of curing, the intensity and type of light unit used for curing.³⁶ Pre-heated composite resins exhibit increased monomer mobility and vibration due to the higher thermal energy of preheated resins, which leads to a lower viscosity than composite resins at room temperature and enhanced mobility of growing chain moieties in the resin material. As a result, DP increases while surface microhardness declines (microhardness indirectly expresses viscosity).^{9,14,37} These studies support Awliya (2007), who stated that composite resin stored at low temperatures result in low VHN values.³⁵ Another study stated that composite resin preheated to 3°C warmer than body temperature (40°C) flowed better and was significantly harder than composite resins inserted into teeth at room temperature.^{38,39} Preheating resin can be clinically beneficial, due to a superior marginal adaptation.²⁶

In our study, DP values did not align with VHNs, which agreed with another study that found there was no correlation between the DP and VHN. We found no significant increase for DP with increasing storage temperature, but there were significant increases in VHN with temperature. Although VHN can correlate well with DP for some composite resins based on temperature, VHN cannot be used to predict DP when different composite resins are being compared mainly because all resins are composed a different mixture of monomers; thus, each type of resin has its specific relationship between DP and its mechanical properties. 7.35 Commented [Editor35]: Remark: The intensity of what? Please specify. Commented [DP36R35]: The intensity of light

Commented [Editor37]: Remark: Lower than what? Please specify.
Commented [DP38R37]: Lower than resin at room

temperature

Commented [Editor39]: Remark: Define what aspect of correlation you mean. Temperature?
Commented [DP40R39]: yes

CONCLUSIONS

Elevating the storage temperature of bulk-fill composite resin from 5°C (refrigerated condition) to (25°C) (typical ambient room temperature) to 35°C (air temperature in hot climates) did not significantly affect a resin's degree of polymerization, but it did significantly increased surface hardness.

REFERENCES

- Tsujimoto A, Barkmeier W, Fischer N, Nojiri K, Nagura Y, Takamizawa T, Latta M. Wear of Resin Composites: Current Insights into Underlying Mechanisms, Evaluation Methods and Influential Factors. The Japanese Dental Science Review 2018;54(2):76-87.
- Rodrigo B, Esteves L, Luís RMM. Bulk-Fill Resin-Based Composites. Advances in Dentistry & Oral Health 2017;4(5):555648.
- Alshaafi MM. Factors Affecting Polymerization of Resin-Based Composites: A Literature Review. The Saudi Dental Journal 2017;29(2):48-58.
- Zorzin J, Maier E, Harre S, Fey T, Belli R, Lohbauer U, et al. Bulk-Fill Resin Composites: Polymerization Properties and Extended Light. Dental Materials 2015;3(1):293-301.
- Gonçalves F, Campos LMP, Rodrigues E, Costa FV, Marques PA, Francci CE, et al. A Comparative Study of Bulk-Fill Composites: Degree of Conversion, Post-Gel Shrinkage and Cytotoxicity. Brazilian Oral Research 2018;32:1-9.

- Dionysopoulos D, Tolidis K, Gerasimou P. The Effect of Composition Temperature and Post-Irradiation Curing of Bulk Fill Resin Composites on Polymerization Efficiency. Materials Research 2016;19(2):466-73.
- Abed YA, Sabry HA, Alrobeigy NA. Degree of Conversion and Surface Hardness of Bulk-Fill Composite Versus Incremental-Fill Composite. Tanta Dental Journal 2015;12:71-80.
- Kelić K, Matić S, Marović D, Klarić E, Tarle Z. Microhardness of Bulk-Fill Composite Materials. Acta Clinica Croatica 2016;55:607-14.
- Dionysopoulos D. Papadopoulos C. Koliniotou-Koumpia E. Effect of Temperature Curing Time and Filler Composition on Surface Microhardness of Composite Resins. Journal of Conservative Dentistry 2015;18(2):114-8.
- Langalia A, Buch A, Khamar M, Patel P. Polymerization Shrinkage of Composite Resins: A Review. Journal of Medical and Dental Science Research 2015;2(10):23-7.
- Galvão MR, Caldas SGFR, Bagnato VS, De Souza Rastelli AN, De Andrade MF. Evaluation of Degree of Conversion and Hardness of Dental Composites Photo-Activated with Different Light Guide Tips. European Journal of Dentistry 2013;7(1):86-93.
- Jerri BA. Evaluate Polymer Degree of Conversion of Bulk-Fill Composite Restoration. IOSR Journal of Dental and Medical Sciences 2015;14(9):75-9.
- Collares FM, Portella FF, Leitune VC, Samuel SM. Discrepancies in Degree of Conversion Measurements By FTIR. Brazilian Oral Research 2014;28(1):1-7.

- 14. Chaves FO, Farias NC, Medeiros LC, Alonso RC, Di Hipòlito V, D'Alpino PH. Mechanical Properties of Composites as Functions of The Syringe Storage Temperature and Energy Dose. Journal of Applied Oral Science 2015;23(2):120-8.
- 15. Calheiros FC, Daronch M. Rueggeberg FA. Effect of Temperature on Composite Polymerization Stress and Degree of Conversion. Dental Materials 2014;24(2):6-11.
- 16. Nainan MT, Balan AK, Sharma R, Thomas SS, Deveerappa SB. The Comparison of The Effects of Different Whitening Toothpastes on The Micro Hardness of A Nano Hybrid Composite Resin. Journal of Conservative Dentistry 2014;17:550-4.
- Al-Mansour K, Al-Sada A, Al-Sinan H. Curing Depth of Bulk-Fill Composites-An In-Vitro Study 1. Pakistan Oral & Dental Journal 2015;35(2):270-4.
- Kusumastuti KS, Irawan B, Damiyanti M. Effect of Shelf Life on Compressive Strength of Type Iv Gypsum. Journal of Physics: Conference Series 2017. 884 012092
- Tauböck TT, Tarle Z, Marovic D, Attin T. Pre-Heating of High-Viscosity Bulk-Fill Resin Composites: Effects on Shrinkage Force and Monomer Conversion. J Dent 2015;43(11):1358-64.
- 20. Hatrick CD, Eakle WS. Dental Materials: Clinical applications for dental assistants and dental hygienists. 3rd ed. Missouri: Elsevier;2016:66-75
- 21. Osternack FHR, Caldas DBM, Rached RN, Vieira S, Platt JA, Almeida JB. Impact of refrigeration on The Surface Hardness of Hybrid and Microfilled Composite Resins. Brazilian Dental Journal 2009;20(1):42-7.

- Castro FLA, Campos BB, Bruno KF, Reges RV. Temperature and Curing Time Affect Composite Sorption and Solubility. Journal of Applied Oral Science 2013;21(3):157-62.
- 23. Loguercio AD, Salvalaggio D, Piva AE, Klein-Júnior CA, Accorinte MLR, Meier MM, et al. Adhesive Temperature: Effects on Adhesive Properties and Resin-Dentin Bond Strength. Operative Dentistry 2011;36(3):293-303.
- 24. Kim E-H, Jung K-H, Son S-A, Hur B, Kwon Y-H, Park J-K. Effect of Resin Thickness on The Microhardness and Optical Properties Of Bulk-Fill Resin Composites. Restorative Dentistry & Endodontics 2015;40(2):128-35.
- 25. Harahap K, Yudhit A, Sari F. Effect of Bench Time Polymerization on Depth of Cure of Dental Composite Resin. IOP Conference Series: Materials Science and Engineering 2017;223:012062:1-6.
- 26. Lohbauer U, Zinelis S, Rahiotis C, Petschelt A, Eliades G. The Effect of Resin Composite Pre-Heating on Monomer Conversion and Polymerization Shrinkage. Dental Materials 2009;25(4):514-9.
- 27. Oliveira M, Cesar PF, Giannini M, Rueggeberg FA, Rodrigues J, Arrais CA. Effect of Temperature on The Degree of Conversion and Working Time of Dual-Cured Resin Cements Exposed To Different Curing Conditions. Operative Dentistry 2012;37(4):370-9.
- 28. Froes-Salgado NR, Silva LM, Kawano Y, Francci C, Reis A, Loguercio AD. Composite Pre-Heating: Effects on Marginal Adaptation, Degree of Conversion and Mechanical Properties. Dental Materials 2010;26:908-14.

- Filho JD, Poskus LT, Guimarães JG, Bacellos AA, Silva EM. Degree of Conversion and Plasticization of Dimethacrylate-Based Polymeric Matrices: Influence of Light-Curing Mode. Journal of Oral Science 2008;50(3):315-21.
- 30. Gajewski VE, Pfeifer CS, Frões-Salgado NR, Boaro LC, Braga RR. Monomers Used in Resin Composites: Degree of Conversion Mechanical Properties and Water Sorption/Solubility. Brazilian Dental Journal 2012;23(5):508-14.
- Singh S. Rajkumar B. Gupta V. Bhatt A. Current Photoinitiator In Dental Materials. International Journal of Applied Dental Science 2017;3(1):17-20.
- 32. Ayub KV, Santos GC Jr, Rizkalla AS, Bohay R, Pegoraro LF, Rubo JH, Santos MJ. Effect of Preheating on Microhardness and Viscosity Of 4 Resin Composite. Journal of Canadian Dental Association. 2014;80:E12. P.1-8.
- 33. Jafarzadeh-Kashi TS, Fereidouni F, Khoshroo K, Heidari S, Masaeli R, Mohammadian M. Effect of Preheating on the Microhardness of Nanohybrid Resinbased Composites. Frontiers in Biomedical Technologies 2015;2(1):15-22.
- Dionysopoulus D. Bulk Fill Composite Resins. A Novelty in Resin-Based Restorative Materials. ARC Journal of Dental Science. 2016;1(2):1-3.
- 35. Leprince JG, Palin WM, Vanacker J, Sabbagh J, Devaux J, Leloup G. Physico-Mechanical Characteristics of Commercially Available Bulk-Fill Composites. Journal of Dentistry 2014;42(8):993-1000.
- 36. Soliman E, Elgayar IL, Kamar AA. Effect of Preheating on Microleakage And Microhardness of Composite Resin. Alexandria Dental Journal 2016;41:4-11.

- 37. Alshaafi MM. Effects of Different Temperature and Storage Time on The Degree of Conversion and Microhardness of Resin-Based Composite. The Journal of Contemporary Dental Practice 2016;3:217-23.
- Awliya WY. The Influence of Temperature on The Efficacy of Polymerization of Composite Resin. The Journal of Contemporary Dental Practice 2007;8(6):009-16.
- Walter R, Edward JS, Sheikh H, Ferracane JL. Effects of Temperature on Composite Resin Shrinkage. Quintessence International 2009;40(10):843-7.

Composite resin	Manufacturer	Composition	Filler content (% weight)
Tetric® N Ceram Bulk-Fill	Ivoclar Vivadent, Schaan, Liechtenstein	bisphenol A diglycidyl ether dimethacrylate (Bis-GMA), urethane dimethacrylate (UDMA), Ba-Al-Si glass, prepolymerized filler (monomer, glass filler, and ytterbium fluoride), spherical mixed oxide	75–77

Table 1. Composition, manufacturer, and filler content of the tested composite resins.

Table 2. Degree of polymerization (DP) relative to temperature for bulk-fill composite

resin.

Treatment Group	%DP mean ± SD	Р	
Temperature 5°C	36.67 ± 0.82	0.454	-
Temperature 25°C	37.17 ± 2.48		
Temperature 35°C	38.17 ± 2.40		

One-way ANOVA

Not significant (P > 0.05)

Table 3. Vicker's hardness number (VHN) relative to storage temperature for all tested

groups.

Treatment group	Mean \pm SD (VHN)	Р	
Temperature 5°C	$49.22\pm0.57^{\rm A}$	0.000*	
Temperature 25°C	51.94 ± 0.79^{B}	0.000*	
Temperature 35°C	53.86 ± 0.41^{C}	0.000*	

 $\hline Means with the different uppercase superscript letters were significantly different from one another at P <$

0.05.

*Significant (P < 0.05).